



NO-TILL SEEDER

The NTS26 No-Till Seeder, available in 7' (2.1m), 9' (2.7m) & 11' (3.4m) widths, makes quick work of renovating pastures, reclaiming rights-of-way, and planting food plots. Designed with ease of use in mind, the NTS26 Series Seeder comes with a variety of built-in features. Metering is ground-driven by the rear packer-roller. Any of the seed boxes can easily be disengaged with simple lockout pins on each drive sprocket, or all the boxes can be locked out with one pin on the main sprocket.



NO-TILL SEEDER MODELS

No-Till Seeder	Working Width	Transport Width	Transport Height	Engine H.P. Required	Weight
NTS2607	7'2" (2.2m)	8'1" (2.5m)	N/A	40-60	851-1,270kg
NTS2609	8'4" (2.5m)	9'4" (2.8m)	N/A	50-85	948-1,417kg
NTS2611	10' (3m)	11'9" (3.6m)	N/A	60-110	1,202-1,724kg

See www.greatplainsag.com for complete specifications.

CAPABLE
3 BOX 3 SEED 3 RATE
3 3 3



NTS2607



NTS2609



NTS2611

NTS2611 with optional pull package.

ADDITIONAL STANDARD FEATURES

- Straight rear roller: 11-3/8" diameter, notched, cast gray iron rings
- Dual front spiked rollers are adjustable up to 18°
- Roller spike: 5/8" x 2", heat-treated steel, replaceable
- Formed plate A-frame
- 3" x 4" tube frame
- Heavy-duty lid w/ seed splash guard
- Seed box lockouts
- Anti-reverse clutch to prevent seed cup damage
- Wide range of calibration settings
- Wind-guarded seed drop
- Lift hooks
- LED safety lighting

*only available by ordering through Parts

OPTIONS

(see website for complete list of features & options)



PULL-TYPE OPTION



NATIVE GRASS BOX




DIGITAL ACREMETER


FEATURES & BENEFITS

METERING COMPONENTS

All three boxes utilize the same proven metering components found in all Great Plains seeding equipment. These three metering systems allow the No-Till Seeder to plant a wide variety of crops, from the smallest clovers to the fluffiest native grasses.



Main Box



Small Seeds Box



Native Grass Box (optional)




CHOOSE 3-POINT OR PULL-TYPE

The unique design allows the machine to be converted from a 3-point to a pull-type by adding a tongue and hydraulic gauge wheels.



ADJUSTABLE FRONT ROLLER

Manually-adjustable front roller controls how aggressively soil is prepped for the seedbed. Run with minimum soil disturbance or set the angle for more aggressive tillage.




3-SPEED TRANSMISSION

A simple and easy repositioning of the drive gear allows for three drive speeds (high, low, and low reduction) and one neutral position.



GROUND-DRIVE ROLLER

The rear packer (roller) utilizes spikes to drive the metering unit while firming seed in place.



SMALL SEEDS BOX

Provides accurate metering of the smallest seeds.